



CUSHMAN®

SHUTTLE 2+2



MOVING PEOPLE, SAVING TIME.

The Cushman® Shuttle 2+2 is the ideal choice for transporting personnel and visitors around a plant, resort, or the jobsite. Comfortably seating up to four passengers with generous bench seats, the rear seat will also convert to a cargo deck. The Shuttle 2+2 is offered in your choice of a fuel-efficient 13.5-hp EFI petrol-powered engine, 48-Volt DC or 72-Volt* AC electric powertrain.

LET'S WORK.

13.5HP
EFI PETROL

48V
DC ELECTRIC

72V*
AC ELECTRIC

362KG
LOAD
CAPACITY

113KG
DECK LOAD
CAPACITY

4
PASSENGER



CUSHMAN® SHUTTLE 2+2



**BRUSH GUARD
AND HEADLIGHTS**



**CONVERTIBLE REAR SEAT
TO CARGO AREA**

— BRAKE LIGHTS (OPTIONAL)



**WINDSHIELD AND
CANOPY (OPTIONAL)**

OPTIONS & ACCESSORIES

- LED Headlights
- 4-Way Turn Signals
- Sun Canopy
- Windshield
- Weather Enclosure
- Hour Meter
- 12 Volt Outlet
- Strobe Light
- Locking Glove Box Door
- Rear Mirrors

	48-VOLT DC ELECTRIC	72-VOLT* AC ELECTRIC	EFI PETROL
BODY & CHASSIS			
FRAME	Welded Steel with DuraShield Powder Coat		
BODY & FINISH	Injection Molded TPO		
STANDARD COLOUR	Patriot Blue		
DIMENSIONS			
OVERALL LENGTH	275.6 cm (108.5 in)	275.6 cm (108.5 in)	275.6 cm (108.5 in)
OVERALL WIDTH	123.2 cm (48.5 in)	125.7 cm (49.5 in)	123.2 cm (48.5 in)
OVERALL HEIGHT	118.1 cm (46.5 in)	120.7 cm (47.5 in)	118.1 cm (46.5 in)
OVERALL HEIGHT (w/ CANOPY)	195.6 cm (77.0 in)	196.9 cm (77.5 in)	195.6 cm (77.0 in)
WHEEL BASE	166.4 cm (65.5 in)	170.2 cm (67.0 in)	166.4 cm (65.5 in)
FRONT WHEEL TRACK	97.8 cm (38.5 in)	87.6 cm (34.5 in)	87.6 cm (34.5 in)
REAR WHEEL TRACK	98 cm (38.5 in)	97.8 cm (38.5 in)	97.8 cm (38.5 in)
GROUND CLEARANCE	11.4 cm (4.5 in)	14.6 cm (5.75 in)	11.4 cm (4.5 in)
LOAD DECK WIDTH	101.6 cm (40.0 in)	101.6 cm (40.0 in)	101.6 cm (40.0 in)
LOAD DECK LENGTH	81.3 cm (32.0 in)	81.3 cm (32.0 in)	81.3 cm (32.0 in)
POWER			
POWER SOURCE	48-Volt DC	72-Volt* AC	4 Cycle 24.5 cu in (401 cc)
MOTOR TYPE	Shunt Wound	AC Induction	Single Cylinder OHV
HORSEPOWER (KW)	8.5 hp (6.3kW) Peak	22.4 hp (16.7 kW) Peak	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	48-Volt	72-Volt*	Starter/Generator, Solid State Regulator
BATTERY (QTY/TYPER)	Six, 8 Volt Deep Cycle	Six, 12 Volt Deep Cycle	One, 12 Volt Maintenance Free
KEY OR PEDAL START	Pedal	Pedal	Pedal
AIR CLEANER	N/A	N/A	Replaceable Dry Cartridge
SPEED CONTROLLER	250 Amp Solid State Controller	350 Amp AC	N/A
OIL FILTER	N/A	N/A	Spin-On
COOLING SYSTEM	N/A	N/A	Air Cooled
FUEL CAPACITY	N/A	N/A	22.7 L (6.0 Gallon) Tank
DRIVE TRAIN	Motor Shaft Direct Drive	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears	Differential with Helical Gears	Differential with Helical Gears
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse	Key Operated Forward-Neutral-Reverse	Seat Mounted Forward-Neutral-Reverse
REAR AXLE RATIO	12.44:1	17:1	11.47:1 (Forward) 14.35:1 (Reverse)
PERFORMANCE			
SEATING CAPACITY	4 Person	4 Person	4 Person
CURB WEIGHT	469.9 kg (1036 lb)	575.2 kg (1268 lb)	896 lb (406.4 kg)
DRY WEIGHT	298.5 kg (658 lb)	360.2 kg (794 lb)	861 lb (390.5 kg)
DECK LOAD CAPACITY	113.4 kg (250 lb)	113.4 kg (250 lb)	250 lb (113.4 kg)
VEHICLE LOAD CAPACITY	362.9 kg (800 lb)	362.9 kg (800 lb)	800 lb (362.9 kg)
OUTSIDE CLEARANCE CIRCLE	5.8 m (19.0 ft)	5.8 m (19.0 ft)	5.8 m (19.0 ft)
SPEED	14.0 mph ± 0.5 mph (22.5 kph ± 0.8 kph)	14 mph ± 0.5 mph (22.5 kph ± 0.8 kph)	14.0 mph ± 0.5 mph (22.5 kph ± 0.8 kph)
STEERING & SUSPENSION			
STEERING	Self-compensating Rack and Pinion		
FRONT/REAR SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers		
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum		
PARKING BRAKE	Self-compensating, Single Point Engagement		
FRONT/REAR TYRES	18 x 8.50 - 8 (4-Ply Rated)	20 x 8.0 - 10 (6-Ply Rated)	18 x 8.5 - 8 (4-Ply Rated)

*Not available in Europe.